

**SC500 F omniflow**

Version number: 1.0

Date of compilation: 04.11.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name	<b>SC500 F omniflow</b>
Registration number (REACH)	not relevant (mixture)
Unique formula identifier (UFI)	RF00-A030-A009-0NW6

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses	Construction Leveling mortar Professional use
--------------------------	---

**1.3 Details of the supplier of the safety data sheet**

Omnicol Flooring BV  
Hambakenwetering 8D-3  
5231 DC 'S Hertogenbosch  
Netherlands

Telephone: +31 073 599 29 25  
e-mail: info@omnicolflooring.eu  
Website: www.omnicolflooring.eu

**1.4 Emergency telephone number**

Emergency information service	This number is only available during the following office hours: Mon-Fri 09:00 - 17:00
-------------------------------	--

Poison centre		
Country	Name	Telephone
Netherlands	Nationaal Vergiftigingen Informatie Centrum (UMC Utrecht) Uitsluitend bestemd om professionele hulpverleners te informeren bij acute vergiftigingen	+31 88 755 8000

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.4S	skin sensitisation	1	Skin Sens. 1	H317

For full text of H-phrases: see SECTION 16

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word Danger

- pictograms

GHS05, GHS07



## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### - hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

### - precautionary statements

P261	Avoid breathing dust.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### - hazardous ingredients for labelling

Contains: Portland Cement; Flue dust, portland cement.

## 2.3 Other hazards

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .



## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture).

### 3.2 Mixtures

The product does not contain (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the product and hence require reporting in this section.

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Portland Cement	CAS No 65997-15-1  EC No 266-043-4  REACH Reg. No Exempt	10 – < 25	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1B / H317 STOT SE 3 / H335		
Flue dust, portland cement	CAS No 68475-76-3  EC No 270-659-9  REACH Reg. No 01-2119486767- 17-xxxx	< 1	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317 STOT SE 3 / H335		

## Remarks

All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.

##### Following skin contact

Brush off loose particles from skin. Rinse skin with water/shower. Wash with plenty of soap and water. Call a POISON CENTER/doctor.

##### Following eye contact

Do not rub the eyes. Mechanical stress can cause damage to the cornea. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a POISON CENTER or doctor if you feel unwell.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the poison centre.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water; Foam; Dry extinguishing powder; ABC-powder;  
Co-ordinate firefighting measures to the fire surroundings.

##### Unsuitable extinguishing media

Water jet.

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous combustion products

During fire hazardous fumes/smoke could be produced. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

##### Special protective equipment for firefighters

Self-contained breathing apparatus (EN 133). Standard protective clothing for firefighters.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety. Control of dust.

##### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Use personal protective equipment as required.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Take up mechanically.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas.

- specific notes/details

Dust deposits may accumulate on all deposition surfaces in a technical room.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- explosive atmospheres

Removal of dust deposits.

- flammability hazards

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

- incompatible substances or mixtures

Keep away from alkalis, oxidising substances, acids.

Control of effects

Protect against external exposure, such as

High temperatures. UV-radiation/sunlight.

Consideration of other advice

Store in a well-ventilated place. Keep container tightly closed.

- ventilation requirements

Use local and general ventilation.

- packaging compatibilities

Keep only in original container.

### 7.3 Specific end use(s)

See section 1.2.

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### National limit values

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Notation	Source
EU	crystalline silica	14808-60-7	IOELV		0,1			dust, r	2017/2398/EU
NL	silica, crystalline - quartz	14808-60-7	GW		0,075			r, dust	SC-SZW

##### Notation

dust as dust

r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

##### Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Flue dust, portland cement	68475-76-3	DNEL	0,84 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Flue dust, portland cement	68475-76-3	DNEL	4 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
Flue dust, portland cement	68475-76-3	DNEL	0,84 mg/m <sup>3</sup>	human, inhalatory	consumer (private households)	chronic - local effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Flue dust, portland cement	68475-76-3	PNEC	282 µg/l	aquatic organisms	water	intermittent release
Flue dust, portland cement	68475-76-3	PNEC	282 µg/l	aquatic organisms	freshwater	short-term (single instance)
Flue dust, portland cement	68475-76-3	PNEC	28 µg/l	aquatic organisms	marine water	short-term (single instance)
Flue dust, portland cement	68475-76-3	PNEC	6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Flue dust, portland cement	68475-76-3	PNEC	875 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Flue dust, portland cement	68475-76-3	PNEC	88 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
Flue dust, portland cement	68475-76-3	PNEC	5 mg/kg	terrestrial organisms	soil	short-term (single instance)

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation. Provide eyewash stations and safety showers at the workplace.

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection (EN 166).

Skin protection



Protective clothing (EN 340 & EN ISO 13688).

Hand protection



Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- type of material

IIR: isobutene-isoprene (butyl) rubber, Nitrile rubber, Butyl rubber

- material thickness

Use gloves with a minimum material thickness:  $\geq 0,38$  mm.

- breakthrough time of the glove material

Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Full face mask/half mask/quarter mask (EN 136/140). P2 (filters at least 94 % of airborne particles, colour code: White). Type: ABEK-P2 (combined filters against gases, vapours and particles, colour code: Brown/Grey/Yellow/Green/White).

Environmental exposure controls

Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	solid (powder)
Colour	grey
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	non-combustible
Lower and upper explosion limit	LEL: 15 g/m <sup>3</sup> UEL:
Flash point	not applicable
Auto-ignition temperature	>200 °C (relative self-ignition temperature for solids)

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

	calculated value, referring to a component of the mixture
Decomposition temperature	no data available
pH (value)	not applicable
Kinematic viscosity	not relevant
Solubility	not determined

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	not determined
-----------------	----------------

### Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	no data available
--------------------------	-------------------

## 9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
Other safety characteristics	there is no additional information

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is not reactive under normal ambient conditions.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### Hints to prevent fire or explosion

The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

### 10.5 Incompatible materials

Oxidisers.

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

**SC500 F omniflow**

Version number: 1.0

Date of compilation: 04.11.2024

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification according to GHS (1272/2008/EC, CLP)****Acute toxicity**

Shall not be classified as acutely toxic.

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Flue dust, portland cement	68475-76-3	oral	LD50	>1.848 mg/kg	rat
Flue dust, portland cement	68475-76-3	inhalation: dust/mist	LC50	>6,04 mg/l/4h	rat
Flue dust, portland cement	68475-76-3	dermal	LD50	≥2.000 mg/kg	rat

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Summary of evaluation of the CMR properties**

The product contains substances that are listed on the "SZW-lijst van kankerverwekkende, mutagene en voor de voortplanting giftige stoffen".

**Specific target organ toxicity - single exposure**

Shall not be classified as a specific target organ toxicant (single exposure).

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

**11.2 Information on other hazards****Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

**Other information**

There is no additional information.

**SECTION 12: Ecological information****12.1 Toxicity**

Shall not be classified as hazardous to the aquatic environment.



**SC500 F omniflow**

Version number: 1.0

Date of compilation: 04.11.2024

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Flue dust, portland cement	68475-76-3	ErC50	22,4 mg/l	algae	72 h
Flue dust, portland cement	68475-76-3	NOEC	11,1 mg/l	fish	96 h
Flue dust, portland cement	68475-76-3	NOELR	50 mg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Flue dust, portland cement	68475-76-3	EC50	743 mg/l	microorganisms	3 h

**12.2 Persistence and degradability**

Data are not available.

**12.3 Bioaccumulative potential**

Data are not available.

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0,1\%$ .**12.6 Endocrine disrupting properties**Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0,1\%$ .**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: Transport information****14.1 UN number or ID number**

not subject to transport regulations

**14.2 UN proper shipping name**

not relevant

**14.3 Transport hazard class(es)**

none

**14.4 Packing group**

not assigned

**14.5 Environmental hazards**

non-environmentally hazardous acc. to the dangerous goods regulations

**14.6 Special precautions for user**

There is no additional information.

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### 14.7 Maritime transport in bulk according to IMO instruments

No data available.

#### Additional information for each of the UN Model Regulations

#### **Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information**

Not subject to ADR, RID and ADN.

#### **International Maritime Dangerous Goods Code (IMDG) - additional information**

Not subject to IMDG.

#### **International Civil Aviation Organization (ICAO-IATA/DGR) - additional information**

Not subject to ICAO-IATA.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Relevant provisions of the European Union (EU)

##### Restrictions according to REACH, Annex XVII

Name	Name acc. to inventory	No
Portland Cement	chromium(VI) compounds	47
Flue dust, portland cement	chromium(VI) compounds	47

##### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

None of the ingredients are listed.

##### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

##### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

##### Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

None of the ingredients are listed.

##### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

##### National regulations (Netherlands)

##### SZW-lijst CMR effects

List of carcinogenic, mutagenic and reproductive toxic substances (SZW-lijst)				
Name acc. to inventory	CAS No	Carcinogenicity	Mutagenicity	Reproductive toxicity
lithium carbonate	554-13-2			repr F2 D1A B

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

### Legend

B	Breastfeeding category
D1A	Development category 1A
F2	Fertility category 2
repr	Listed in "NIET-limitative list of reproductive toxic substances"

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2017/2398/EU	Directive of the European Parliament and of the Council amending Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

amended by 2020/878/EU

## SC500 F omniflow

Version number: 1.0

Date of compilation: 04.11.2024

Abbr.	Descriptions of used abbreviations
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NOELR	No Observed Effect Loading Rate
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
SC-SZW	Staatscourant: Regeling van de Minister van Sociale Zaken en Werkgelegenheid tot wijziging van de Arbeidsomstandighedenregeling
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.